


## PRODUCT SHEET FG22703

### TECHNICAL DATA

### LAYOUT

Voltage	12.00 V
Performance	27Ah C20 1.75V/cell 25°C
Float Voltage	2.27V/cell at 20°C
Connection torque	5 - 6 Nm
Max Charge Current	6.75 A
Weight (Typical)	8,20 kg
Internal Resistance	mOhm
Short Circuit Current	A



### ELECTRICAL PERFORMANCES - Including Fiamm connection voltage drop

Constant Current Discharge Table [A] at 20°C

V / cell	5 min	10 min	15 min	30 min	45 min	1 h	2 h	3 h	4 h	5 h	6 h	8 h	10 h
1,60	88,1	61,7	47,1	28,5	20,7	16,5	9,25	6,76		4,45			2,47
1,65	84,8	59,9	46,0	28,2	20,5	16,4	9,19	6,73		4,41			2,45
1,67	82,4	58,8	45,6	28,0	20,3	16,2	9,13	6,68		4,39			2,44
1,70	80,1	57,6	45,1	27,6	20,2	15,9	9,08	6,62		4,36			2,43
1,75	76,2	56,2	43,9	27,1	19,8	15,7	8,91	6,54		4,28			2,39
1,80	60,0	45,5	35,9	22,7	16,9	13,7	7,98	5,87		3,90			2,20
1,85													
1,90													

Constant Power Discharge Table [W/cell] at 25°C

V / cell	5 min	10 min	15 min	30 min	45 min	1 h	2 h	3 h	4 h	5 h	6 h	8 h	10 h
1,60	154	111	86,2	54,8	40,6	32,6	18,5	13,3		8,80			4,89
1,65	149	108	84,8	54,1	40,1	32,2	18,4	13,3		8,77			4,88
1,67	145	106	84,1	53,6	39,6	32,0	18,3	13,2		8,74			4,87
1,70	141	104	83,0	53,1	39,3	31,6	18,2	13,1		8,71			4,85
1,75	134	102	81,7	52,5	38,8	31,3	18,0	13,0		8,59			4,81
1,80	124	96,2	77,7	50,1	37,4	30,1	17,5	12,7		8,45			4,67
1,85	106	82,8	67,4	43,6	33,1	27,0	16,0	11,7		7,89			4,46
1,90													